



THERMAL IMAGING CAMERA FOR FIREFIGHTERS

FLIR K53™

The K53 is an easy-to-use thermal imaging camera (TIC) that offers affordability without sacrificing the reliability, clarity, or performance first responders expect from FLIR. The K53 features FLIR's patented FSX® Flexible Scene Enhancement, which intensifies thermal images' structural and textural details. The enhanced perspective improves firefighters' orientation and tactical decision-making capabilities. First responders gain a sense of confidence and safety as they forge ahead to fight fires and save lives.

www.flir.com/K53



STREAMLINED HIGH PERFORMANCE

Simple, single-button glove-friendly control; straightforward operation

- Compact and lightweight enough to carry anywhere or attach to your gear
- Record images and videos with a simple trigger-pull
- Water-resistant (IP67), and rugged enough to withstand a drop from 2 m (6.6 ft) onto a concrete floor
- Fully operational at temperatures up to 500°F/260°C (max. 5 minutes)



UNCOMPROMISING CLARITY AND RESOLUTION

Detail-rich images help you see clearly and move safely in smoky conditions

- 320 × 240 (76,800 pixel) resolution and a rapid refresh-rate (60 Hz) help orient you on the scene
- FLIR FSX digital processing adds edge detail for greater perspective and increased navigational awareness
- Bright and easy to see 4" LCD display



IMPROVED TACTICAL DECISION-MAKING

High-quality imaging can be standard issue for every firefighter

- Provides clear visual information needed to make crucial tactical decisions
- Fixed temperature scale with TI Basic Mode allows for quick reference in rapidly evolving conditions without confusing changes
- Stores thermal images and video clips to access for on-scene review or to produce scene incident reports

SPECIFICATIONS

Thermal imaging and optical data	
IR resolution	320 × 240 (76,800 pixels)
Refresh rate	60 Hz
Thermal sensitivity/NETD	<30 mK @ 86°F (30°C)
Field of view (FOV)	51° × 38°
Focal plane array	Uncooled microbolometer, 7.5–13 μm
Start-up time	<17 sec (IR image, no GUI)
Image presentation	
Display	320 × 240 pixel, 4 in backlit LCD
Auto-range	Selectable on/off in FLIR Tools
Image modes	Fixed color scale, TI Basic
Flexible Scene Enhancement (FSX®)	Yes
Measurement	
Object temperature range	-4°F to 302°F (-20°C to 150°C); 32°F to 1202°F (0°C to 650°C)
Accuracy	±7.2°F (±4°C) or ±4% of reading for ambient temperature 50°F to 95°F (10°C to 35°C)
Spotmeters	1
Data storage, transfer, and compatibility	
USB type	USB mini-B
Interfaces	Update from PC devices, data transfer to and from PC
Compatibility	Works with FLIR Tools software

Image/video storage	Up to 200 image or video files (max. duration of 5 min)
Video streaming	Uncompressed video over USB
General	
Operating temperature range	-4°F to 185°F (-20°C to 85°C) – infinity; 302°F (150°C) – 15 minutes; 500°F (260°C) – 5 minutes
Storage temperature range	-40°F to 185°F (-40°C to 85°C)
Battery type and voltage	Li-ion, 3.6 V rechargeable
Battery operating time	Approximately 4 hours at 77°F (25°C) and with typical use
Charging time	2 h to 85% capacity
Directives	Designed to meet specifications for the following: • Vibration • Impact acceleration resistance • Corrosion • Viewing surface abrasion • Heat resistance • Heat and flame • Product label durability
Drop	EMC • EN 61000-6-2:2005 (Immunity) • EN 61000-6-3:2011 (Emission) • FCC 47 CFR
Weight w/ battery	1.54 lbs (0.7 kg)
Safety (power supply)	CE/EN/UL/CSA/PSE 60950-1
Size (L × W × H)	4.7 × 4.9 × 11 in (120 × 125 × 280 mm)
Tripod mount	UNC 1/4"-20
Package contents	
K53 TIC, 2 batteries, battery charger, hard transport case, lanyard strap, neck strap, power supply, printed documentation, retractable lanyard, USB cable. Optional truck charger available	



CORPORATE
HEADQUARTERS
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 877.773.3547

NASHUA
FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

CANADA
FLIR Systems, Ltd.
3430 South Service Road
Suite 103
Burlington, ON L7N 3T9
Canada
PH: +1 800.613.0507

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18085-852
Brasil
PH: +55 15 3238 8070

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved.

19-0238-INS

