

# Specs

---

## Aircraft

Dimensions (unfolded, excl. propellers)	470×585×215 mm (L×W×H)
Dimensions (folded)	365×215×195 mm (L×W×H)
Diagonal Wheelbase	668 mm
Weight (incl. two batteries)	3770 ± 10 g
Max Takeoff Weight	3998 g
Operation Frequency <sup>[1]</sup>	2.4000-2.4835 GHz; 5.725-5.850 GHz
Transmitter Power (EIRP)	2.4 GHz: <33 dBm (FCC); <20 dBm (CE/SRRC/MIC) 5.8 GHz: <33 dBm (FCC/SRRC); <14 dBm (CE)
Hovering Accuracy (windless or breezy)	Vertical: ±0.1 m (Vision System enabled); ±0.5 m (N-mode with GPS); ±0.1 m (RTK) Horizontal: ±0.3 m (Vision System enabled); ±1.5 m (N-mode with GPS); ±0.1 m (RTK)
RTK Positioning Accuracy (fixed RTK enabled)	1 cm+1 ppm (horizontal) 1.5 cm+1 ppm (vertical)
Max Angular Velocity	Pitch: 150°/sec.; Yaw: 100°/sec.
Max Tilt Angle	35° (N-mode and Forward Vision System enabled: 25°)
Max Ascent/Descent Speed	6 m/s, 5 m/s
Max Tilt Descent Speed	7 m/s
Max Horizontal Speed	23 m/s
Max Service Ceiling Above Sea Level (without other payload)	5,000 m (with 1671 propellers) 7,000 m (with 1676 propellers)
Max Wind Resistance	15 m/s 12 m/s during taking off and landing
Max Hover Time <sup>[2]</sup>	36 min
Max Flight Time <sup>[2]</sup>	41 min
Motor Model	3511
Propeller Model	1671 1676 High Altitude (not included)
Ingress Protection Rating <sup>[3]</sup>	IP55
GNSS	GPS+Galileo+BeiDou+GLONASS (GLONASS is supported only when RTK module is enabled)

Operating Temperature -20° to 50° C (-4° to 122° F)

## Gimbal

Angular Vibration Range ±0.01°

Controllable Range Pan: ±90°  
Tilt: -120° to +45°

Mechanical Range Pan: ±105°  
Tilt: -135° to +60°  
Roll: ±45°

## Zoom Camera

Sensor 1/2" CMOS, Effective pixels: 48M

Lens Focal length: 21-75 mm (equivalent: 113-405 mm)  
Aperture: f/2.8-f/4.2  
Focus: 5 m to ∞

Exposure Compensation ±3 ev (using 1/3 ev as step length)

Electronic Shutter Speed Auto Mode:  
Photo: 1/8000-1/2 s  
Video: 1/8000-1/30 s  
M Mode:  
Photo: 1/8000-8 s  
Video: 1/8000 -1/30 s

ISO Range 100-25600

Max. Video Resolution 3840×2160

Max Photo Size 8000×6000

## Wide Camera

Sensor 1/2" CMOS, Effective pixels: 12M

Lens DFOV: 84°  
Focal length: 4.5 mm (equivalent: 24 mm)  
Aperture: f/2.8  
Focus: 1 m to ∞

Exposure Compensation ±3 ev (using 1/3 ev as step length)

Electronic Shutter Speed Auto Mode:  
Video:  
1/8000-1/2 s  
Video: 1/8000-1/30 s  
  
M Mode:  
Photo: 1/8000-8 s  
Photo: 1/8000-1/30 s

ISO Range 100-25600

Max. Video Resolution 3840×2160

Photo Size 4000×3000

## Thermal Camera

Thermal Imager	Uncooled VOx Microbolometer
Lens	DFOV: 61° Focal length: 9.1 mm (equivalent: 40 mm) Aperture: f/1.0 Focus: 5 m to ∞
Infrared Temperature Measurement Accuracy <sup>[4]</sup>	±2°C or ±2% (using the larger value)
Video Resolution	Infrared Image Super-resolution Mode: 1280×1024 Normal Mode: 640×512
Photo Size	Infrared Image Super-resolution Mode: 1280×1024 Normal Mode: 640×512
Pixel Pitch	12 μm
Temperature Measurement Method	Spot Meter, Area Measurement
Temperature Measurement Range	High Gain Mode: -20° to 150° C (-4° to 302° F) Low Gain Mode: 0° to 500° C (32° to 932° F)
Temperature Alert	Supported
Palette	White Hot/Black Hot/Tint/Iron Red/Hot Iron/Arctic/Medical/Fulgurite/Rainbow 1/Rainbow 2

## FPV Camera

Resolution	1920×1080
DFOV	161°
Frame Rate	30 fps

## Laser Module

Wavelength	905 nm
Max Laser Power	3.5 mW
Single Pulse Width	6 ns
Measurement Accuracy	±(0.2 m + D×0.15%) D is the distance to a vertical surface
Measuring Range	3-1,200 m (0.5×12 m vertical surface with 20% reflectivity)

## Vision Systems

Obstacle Sensing Range	Forward: 0.6-38 m Upward/Downward/Backward/Sideward: 0.5-33 m
FOV	65° (H), 50° (V)
Operating Environment	Surfaces with clear patterns and adequate lighting (> 15 lux)

## Infrared Sensing Systems

Obstacle Sensing Range	0.1 to 10 m
FOV	30°
Operating Environment	Large, diffuse, and reflective obstacles (reflectivity >10%)

## TB30 Intelligent Flight Battery

Capacity	5880 mAh
Voltage	26.1 V
Battery Type	Li-ion 6S
Energy	131.6 Wh
Net Weight	Approx. 685 g
Operating Temperature	-20° to 50° C (-4° to 122° F)
Storage Temperature	20° to 30° C (68° to 86° F)
Charging Temperature	-20° to 40° C (-4° to 104° F) (When the temperature is lower than 10° C (50° F), the self-heating function will be automatically enabled. Charging in a low temperature may shorten the lifetime of the battery)
Chemical System	LiNiMnCoO2

## Auxiliary Lights

Effective Illumination Distance	5 m
Illumination Type	60 Hz, solid glow

## Remote Controller

Screen	7.02 inch LCD touchscreen, with a resolution of 1920×1200 pixels, and high brightness of 1200 cd/m <sup>2</sup>
Internal Battery	Type: Li-ion (6500 mAh @ 7.2 V) Charge Type: Supports battery station or USB-C charger maximum rated power 65W (max voltage of 20V) Charge Time: 2 hours Chemical System: LiNiCoAlO2
External Battery(WB37 Intelligent Battery)	Capacity: 4920 mAh Voltage: 7.6 V Battery Type: Li-ion Energy: 37.39 Wh Chemical System: LiCoO2
Operating Time <sup>[5]</sup>	Internal Battery: Approx. 3 hours 18 min Internal Battery + External Battery: Approx. 6 hours
Ingress Protection Rating <sup>[3]</sup>	IP54
GNSS	GPS+Galileo+BeiDou
Operating Temperature	-20° to 50° C (-4° to 122° F)

## O3 Enterprise

Operating Frequency <sup>[1]</sup>	2.4000-2.4835 GHz, 5.725-5.850 GHz
Max Transmission Distance (unobstructed, free of interference)	15 km (FCC); 8 km (CE/SRRC/MIC)
Max Transmission Distance (with interference)	Strong Interference (urban landscape, limited line of sight, many competing signals): 1.5-3 km (FCC/CE/SRRC/MIC) Medium Interference (suburban landscape, open line of sight, some competing signals): 3-9 km (FCC); 3-6 km (CE/SRRC/MIC) Weak Interference (open landscape abundant line of sight, few competing signals): 9-15 km (FCC); 6-8 km (CE/SRRC/MIC)
Transmitter Power (EIRP)	2.4 GHz: <33 dBm (FCC); <20 dBm (CE/SRRC/MIC) 5.8 GHz: <33 dBm (FCC); <14 dBm (CE); <23 dBm (SRRC)

## Wi-Fi

Protocol	Wi-Fi 6
Operating Frequency <sup>[1]</sup>	2.4000-2.4835 GHz; 5.150-5.250 GHz; 5.725-5.850 GHz
Transmitter Power (EIRP)	2.4 GHz: <26 dBm (FCC); <20 dBm (CE/ SRRC/MIC) 5.1 GHz: <26 dBm (FCC); <23 dBm (CE/ SRRC/MIC) 5.8 GHz: <26 dBm (FCC/SRRC); <14 dBm(CE)

## Bluetooth

Protocol	Bluetooth 5.1
Operating Frequency	2.4000-2.4835 GHz
Transmitter Power (EIRP)	<10 dBm

## BS30 Intelligent Battery Station

Dimensions	353×267×148 mm
Net Weight	3.95 kg
Compatible Battery Type	TB30 Intelligent Flight Battery WB37 Intelligent Battery
Input	100-240 VAC, 50/60 Hz
Output	TB30 Battery Port: 26.1 V, 8.9 A (supported up to two outputs simultaneously) WB37 Intelligent Battery: 8.7 V, 6 A
Output Power	525 W
USB-C port	Max. output power of 65 W
USB-A port	Max. output power of 10 W (5 V, 2 A)
Power Consumption (when not charging battery)	< 8 W
Output Power (when warming up battery)	Approx. 30 W

<b>Operating Temperature</b>	-20° to 40° C (-4° to 104° F)
<b>Ingress Protection Rating<sup>[3]</sup></b>	IP55 (with the cover closed properly)
<b>Charging Time<sup>[6]</sup></b>	Approx. 30 min (charging two TB30 batteries from 20% to 90%) Approx. 50 min (charging two TB30 batteries from 0% to 100%)
<b>Protection Features</b>	Anti-Backflow Protection Short Circuit Protection Over Voltage Protection Over Current Protection Temperature Protection