

## Vibration Resistant Distortionless Lens

Model		VS-MCA15								
Focal Length(f)		15 mm (15.01)								
Maximum Aperture Ratio		1: 2.0								
Optical Mag. Range		( $\infty$ ) × 0.03 ~ × 0.3								
Optical Mag.		× 0.03		× 0.2			× 0.3			
FOV (V x H)	2/3"	236.7 × 280.0 mm		35.5 × 42.0 mm			23.7 × 28.0 mm			
	1/2"	160.0 × 213.3 mm		24.0 × 32.0 mm			16.0 × 21.3 mm			
	1/3"	120.0 × 160.0 mm		18.0 × 24.0 mm			12.0 × 16.0 mm			
WD		490.7 mm		65.4 mm			40.3 mm			
O/I (Object & Imager Distance)		536.1 mm		113.4 mm			89.8 mm			
Aperture		2	5.6	8	2	5.6	8	2	5.6	8
Working F/#		2.1	5.8	8.2	2.4	6.7	9.6	2.6	7.3	10.4
TV Distortion (2/3")		-0.01 %		-0.13 %			-0.22 %			
Operation		Manual								
Wavelength		Visible								
Mount		C-Mount								
Flange Back		17.526 mm								
Sensor Size (max.)		2/3"								
Filter Thread		M 27 P= 0.5								
Weight (approx.)		42 g								
Dimension		$\phi$ 31 (max.) × L = 27.9 (X0.03) ~ 32 (X0.3) mm								

※ Note: Available with MC Focus Locking System, FNO (Iris Open) 5 .6 & 8